

Metal Mesh Lifting Slings



FEATURES

- Extremely durable.
- Able to handle abrasive or sharp edges materials.
- Able to hold hot or corrosive materials.
- Strong when compared to wire rope and sythetic slings.
- Conforms to shape of material being lifted.
- Easy to rig into a choke or hitch basket.
- Saves money as it will outlast wire rope and sythetic slings.
- Ideal for handling all types of products such as:
 - Coiled strip
 - Thick walled tubing
 - Polished shafting
 - Hot rolled flat bar stock
 - Round bar stock
 - Sheet steel
 - Lumber
 - Paper machine rolls
 - Precast hollow concrete beams
 - Structural Beams


TECHNICAL SPECIFICATIONS

HEAVY DUTY

WIDTH OF SLING		SAFE WORKING LOAD CHOKE HITCH AND STRAIGHT PULL		SAFE WORKING LOAD BASKET HITCH WITH PARALLEL LEGS	
INCH	MM	TONS	KG	TONS	KG
3	76	1	1000	2	2000
5	127	2	2000	4	4000
8	203	3	3000	6	6000
10	254	4	4000	8	8000
12	305	5	5000	10	10000
18	457	7.5	7500	15	15000
24	610	10	10000	20	20000

LIGHT DUTY

WIDTH OF SLING		SAFE WORKING LOAD CHOKE HITCH AND STRAIGHT PULL		SAFE WORKING LOAD BASKET HITCH WITH PARALLEL LEGS	
INCH	MM	TONS	KG	TONS	KG
4	102	0.5	500	1	1000
8	203	1	1000	2	2000
12	305	1.5	1500	3	3000



SIZES

- Heavy Duty Max Width: 24"
- Heavy Duty Max Length: Variable
- Light Duty Max Width: 12"
- Light Duty Max Length: Variable

MATERIALS

- Carbon Steel
- Stainless Steel

LIFTING HANDLES

- Slings can be supplied with or without lifting handles

TO ORDER METAL MESH LIFTING SLINGS PLEASE CONTACT US ON:

01795 228 583

01302 533 111